

Benq MS630ST

Projection System	DLP
Native Resolution	SVGA (800 x 600)
Brightness (ANSI Lumens)	3200 lumens
Contrast Ratio	13000:1
Display Color	1.07 Billion Colors
Lens	F=2.6-2.78, f=10.2-12.24mm
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Throw Ratio	0.9~1.08 (78" @ 1.44m)
Image Size (Diagonal)	60"~120"/ 300"
Zoom Ratio	1.2:1
Lamp(Normal/Economic Mode/SmartEco Mode)*	4000/ 6000/ 6500/ 10000 hours
Keystone Adjustment	1D, Vertical +/- 30 degrees
Projection Offset**	110% ±5%
Resolution Support	VGA (640 x 480) to WUXGA_RB (1920 x 1200) * RB = Reduced Blanking
Horizontal Frequency	15K~102KHz
Vertical Scan Rate	24~120Hz
Lamp Wattage	196W
Interface	Computer In (D-sub 15pin) x 1 (Share with component) Monitor Out (D-sub 15pin) x 1 Composite Video In (RCA) x 1 S-Video In (Mini DIN 4pin) x 1 HDMI (1.4a) x 2 (One share with MHL2.0) Audio In (Mini Jack) x 1 Audio L/R In (RCA) x 1

	Audio Out (Mini Jack) x 1 Speaker 10W x 1 USB (Type mini B) x 1 (Download & Page Up/ Down) USB (Type A) x1 (1.5A Power Supply) RS232 (DB-9pin) x 1 IR Receiver x 2 (Front + Top)
Dimensions(W x H x D)	287.3 x 114.4 x 232.6mm
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
3D Support and Compatibility	PC: 120Hz Frame Sequential 3D for resolutions up to WXGA, PC: 60Hz Top-bottom 3D for resolutions up to SXGA+ Video: 60Hz Frame Sequential 3D for resolutions up to 480i
Weight	2.6kg
Audible Noise	33/ 28 dBA (Normal/ Economic mode)
Power Supply	AC100 to 240V, 50 to 60 Hz
Power Consumption	Normal 305W, Eco 220W, Standby < 0.5W
Power Management Function	Automatic power off after 20 minutes without a display source
On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 Languages)
Picture Modes	** Bright/ Presentation / sRGB/ Cinema /(3D) / User 1/ User 2
Accessories (Standard)	Remote Control w/ Battery Power Cord (by region) User Manual CD Quick Start Guide Warranty Card (by region)

	VGA (D-sub 15pin) Cable
Accessories (Optional)	Presentation Plus: P/N: 65.J9306.002 Spare Lamp Kit: P/N: 5J.J9V05.001 Ceilling Mount: P/N: 5J.J2K01.001 3D Glasses: P/N: 5J.J9H25.001 Carry bag