## ThinkCentre Tiny-In-One 24 Gen3 10QXPAT1++

**Product** 

ThinkCentre Tiny-in-One 24 Gen3

Region

**EMEA** 

Machine Type

10QX

Color Black

Display Size

23.8"

Multi-touch

10-point Multi-touch

Resolution

1920x1080

Aspect Ratio

16:9

Pixel Pitch

0.2745 mm

Dot / Pixel Per Inch

92.6 dpi

**Brightness** 

250 nits

Contrast Ratio

1000:1

Pixel Response Time

4-14 ms

Color Gamut

72%

View Angle (H / V)

178 / 178

Stand

Adjustable Stand

Power Comsuption (Typical / Maximum)

19W / 32W

**Power Supply** 

90W 88% Adapter

Warranty

3-year

Ann Date (mm/yy)

07/17

Note:

\* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "\*\*" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries



## WWW.LENOVO.COM

This publication was developed for products and services oered in the United States and E.M.E.A countries. Lenovo may not oer the products, services or features discussed in this document in other countries. Lenovo may withdraw an oering at any time. Information is subject to change without notice. Consult your local representative for information on oerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.



## http://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2017. All rights reserved.

## ThinkCentre Tiny-in-One (TIO) 24 Gen3

Model	Non-touch model: Touch model:	10QYPAR1++/10QYPA 10QXPAR1++/10QXPA			
Form factor	Tiny-in-One, offers a full All-In-One experience when optional Tiny slots into				
Compatible Tiny:	the back of TIO, clean cabling and effortless setup M910 / M710 / M900 / M700 / M600 / M715 / M93/p* / M83 / M73* / M53 / Chromebox Tiny				
		can't be turned on by pr	essing power button of TIO		
Panel	TFT-LCD, In-Plane Switching technology**, White LED backlight Notes: In-Plane Switching may refer to VA, PLS, and IPS panels				
Viewable image size	23.8" (604.7mm) diagonal 21.06" x 12.23" (525.0mm x 212.0mm				
Max view area (W x H) Bezel Width	21.06" x 12.32" / 535.0mm x 313.0mm Top / Side: 2mm, Bottom: 22.1mm				
Native resolution	1920x1080				
Multi-touch Aspect ratio	Optional 10-point multi-touch, supports Wake on Touch 16:9				
Pixel pitch (mm)	0.2745mm				
Dot/Pixel per Inch	92.6 dpi				
Brightness Contrast ratio	250 nits or cd/m² (typical) 1000:1 (typical)				
Pixel response time	14ms (default), over drive to 4ms, 6ms				
Color gamut Anti-reflective	72% Anti-glare				
Viewing angle at 10:1 C		ontal, 178° (+/- 89°) ver	tical		
Preset resolutions	640x350 @ 70Hz	,			
	640x480 @ 60Hz, 67Hz, 72Hz, 75Hz 720x400 @ 70Hz				
800x600 @ 60Hz, 72Hz, 75Hz 1024x768 @ 60Hz, 70Hz, 75Hz					
	1152x864 @75Hz 1280x800 @ 60Hz				
	1280x1024 @ 60Hz, 72Hz, 75Hz				
1366x768 @ 60Hz					
	1440x900 @ 60Hz, 75Hz 1600x1200 @ 60Hz, 70Hz, 75Hz				
	1680x1050 @ 60H	Z			
Droots / waar aattings	1920x1080 @ 60H				
Presets / user settings On seroon display	Presets: 25; user so		(8 Janguagos)		
On screen display Control features	On screen display with digital user controls (8 languages) Ftont: Exit button, Left / Mode-switching button (TIO / monitor mode), Right / Brightness button, Enter / Menu button, Power button				
Tiny in One Dower On		ip button, Volume down			
Tiny-in-One Power On		Pressing Alt + P on keyboard or pressing Power button positioned on TIO can turn on both TIO and Tiny (only some Tiny support, see compatible list)			
Side ports (TIO)	One USB 3.1 Gen1 / USB 2.0 (when M73 or M53 installed or USB 2.0				
	connected via USB upstream port)  Notes: The USB port is only available when a Tiny is istalled or a PC is				
		via USB upstream port	Tra riny is istalled of a r O is		
Side ports (Tiny)	Side ports offered by installed Tiny (optional)				
Rear ports 3-in-1 Cable	One DisplayPort in port, one USB upstream port, one power connector Undetachable 3-in-1 cable (Power connecter, USB [supports USB 3.1 Gen1]				
o III-I Oabic	/ USB 2.0], DisplayPort), only for connecting to Tiny installed (optional)				
Camera	1080p camera with dual microphone for VOIP, LED indicator				
Internal Speaker	2 watt x2				
Security	Security keyhole for attachment of optional cable lock (Kensington® lock compatible), locks optional Tiny with TIO together, more security features offered by Tiny installed (optional)				
Mechanical	Dimensions	TIO without stand	TIO with stand		
	W x D x H (inch)	21.25 x 2.85 x 14.47	21.25 x 11.11 x 15.72 - 20.06		
	W x D x H (mm)	539.8 x 72.5 x 367.6	539.8 x 282.3 x 399.4 - 509.4		
	Weight (Approx.)	7.96 lb /3.61 kg	12.92 lb /5.86 kg		
	weight (Approx.)	7.30 ID /3.01 kg	12.32 ID /3.00 kg		

Mounting features	Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)		
Adjustable stand	Tilt: 30° back, -5° forward;		
	swivel: +/-45°:		
	Pivot: clockwise 0° to 90°		
Power supply	90 watts AC/DC adapter, 88% PSU, universal		
Power consumption	19 watts typical, 32 watts maximum, <0.5 watts standby / suspend		
Limited warranty	3-years, Customer Carry-In or Mail-In via Rapid Replacement Service		
VESA-compliant	VESA DDC2B/CI, VESA DPMS-compliant		
Ergonomics	ISO 9241-307, TUV Eye Comfort certified		
Emission standards	FCC Class B		
Environmental	TCO 7.0, TCO Edge 2.0, WEEE, RoHS, ENERGY STAR® 7.0, EPEAT™ Gold rating, ULE Gold, TUV, VOC		
Windows certifications	Windows 7 and Windows 10 certified		
Ship group	TIO 24 (Monitor), detachable stand, AC/DC power adapter, power cord, user's guide and driver CD, quick start and safety poster		
Accessories	For compatible accessories, please go to http://www.lenovoquickpick.com		

ThinkCentre Tiny-in-One 24 Gen3 Compatible list					
Model	M910 / M710 / M900 / M700 /	M93/p Tiny,	Chromebox		
	M600 / M715 / M83 / M53 Tiny	M73 Tiny			
Turn on TIO and					
Tiny together via	All models	All models	Not support		
Alt + P on USB KB					
Turn on TIO and					
Tiny together via	All models	TIO models	All models		
TIO Power Button					











