Samsung V-NAND SSD 970 EVO Plus

2019 Data Sheet

Revision 1.0



SAMSUNG

DISCLAIMER

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein may change without notice and is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office.

COPYRIGHT © 2019

This material is copyrighted by Samsung Electronics. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

TRADEMARKS & SERVICE MARKS

The Samsung Logo is the trademark of Samsung Electronics. Adobe is a trademark and Adobe Acrobat is a registered trademark of Adobe Systems Incorporated. All other company and product names may be trademarks of the respective companies with which they are associated.

Revision History

Revision Number	Description	Revision Date
1.0	Initial Release	Jan., 2019

SAMSUNG

Samsung SSD 970 EVO Plus

The Samsung SSD 970 EVO Plus is a client PC NVMe SSD with Samsung's latest 3-bit MLC V-NAND. The 970 EVO Plus is specially designed for tech enthusiasts, hardcore gamers, and professionals who need unrivaled performance, superior reliability, and it boasts the best-in-class capacity for intensive workloads on PCs and workstations.

Unrivaled Performance

In combination with the latest Samsung V-NAND technology and firmware optimization, the 970 EVO Plus achieves random write speeds up to 57% faster than the 970 EVO. Also, it offers industry-leading sequential performance among NVMe SSDs with read/write speeds of up to 3,500/3,300 MB/s, respectively. The 970 EVO Plus performance will be the industry-leading and maximum within the current PCIe Gen3 interface.

Superior Reliability

The 970 EVO Plus boasts exceptional endurance with up to 600 terabytes¹⁾ written. Advanced thermal control solutions enhance performance with reduced heat risk. Dynamic Thermal Guard (DTG) technology proactively prevents overheating, and a heat spreader with an integrated thin copper film dissipates heat more efficiently. A nickel coating on the Phoenix controller also helps to dissipate heat faster during heavy workload use in order to ensure the high levels of quality and reliability for which Samsung is known. The 970 EVO Plus comes with an industry-leading 5-year warranty.

1) All documented endurance test results are in compliance with JESD218 standards. Please visit www.jedec.org for detailed information.

System Design Flexibility

The 970 EVO Plus enables convenient storage expansion across many different devices. The 970 EVO Plus comes in a broad range of capacity options, made possible through Samsung's latest V-NAND technology. In addition, the 970 EVO Plus offers high power efficiency as well as exceptional speeds, making it the ideal solution to use with application ranging from ultra-thin computing to high-performance computing systems.

Advanced Data Encryption

The 970 EVO Plus provides multiple advanced data encryption features like Self-Encrypting Drive (SED) security technology that will help keep data safe at all times. The 970 EVO Plus includes an AES 256-bit hardware-based encryption engine to ensure that your personal files remain secure. The 970 EVO Plus is compliant with various advanced security management solutions (such as, TCG Opal and Encrypted Drive-IEEE1667).

Samsung Data Migration and Magician Software

Samsung Magician and Data Migration software supports the 970 EVO Plus. These powerful software programs offer consumers an easy way to manage their Samsung SSDs. With Magician, users can instantly gain an overview of critical drive information and compatibility issues. Users will find and implement the process of keeping their firmware, drivers and other settings up to date easier than ever.

The Samsung Data Migration software is simple to use – yet provides a very powerful "Custom Cloning" feature that enables migration work even when source data is greater than the SSD's capacity.

TECHNICAL SPECIFICATIONS

Samsung SSD 970 EVO Plus						
Usage Application	Client PCs					
Interface	PCIe Gen 3.0 x4, NVMe 1.3					
	Capacity ¹⁾		250GB	500GB	1TB	
	Controller		Samsung Phoenix Controller			
Hardware Information	NAND Flash Memory		Samsung V-NAND 3bit MLC			
	DRAM Cache Memory		512MB LPDDR4 1GB LPDDR4		1GB LPDDR4	
	Dimension		Max 80.15 x Max 22.15 x Max 2.38 (mm)			
	Form Factor		M.2 (2280) ²⁾			
	Sequential Read		3500 MB/s			
	Seque	ential Write	2300 MB/s	3200 MB/s	3300 MB/s	
Performance	QD1	Ran. Read	17K IOPS	19K	IOPS	
(Up to.) ^{3) 4)}	Thread 1	Ran. Write		60K IOPS		
	QD 32	Ran. Read	250K IOPS	480K IOPS	600K IOPS	
	Thread 4	Ran. Write		550K IOPS		
	Idle (ASPT on)		30mW			
Power	Active	Read	5 W	5.5 W		
Consumption ⁵⁾	(Avg.)	Write	4.2 W	5.8 W	6 W	
	L1.2 mode		5 mW			
	Temp.	Operating	0°C to 70°C (Measured by S.M.A.R.T. Temperature Proper airflow recommended)		irflow recommended)	
		Non-Operating	-45°C to 85°C			
Reliability	Humidity		5% to 95% non-condensing			
	Shock	Non-Operating	1,500G(Gravity), duration: 0.5ms, 3 axis		ms, 3 axis	
	Vibration	Non-Operating	20~2,000Hz, 20G			
	MTBF		1.5 million hours			
) // (TBW ⁶⁾⁷⁾		150TB	300TB	600TB	
Warranty ⁹⁾	Period		5 years limited ⁸⁾			
Supporting Features	TRIM (Required OS support), Garbage Collection, S.M.A.R.T					
Data SecurityAES 256-bit Full Disk Encryption, TCG/Opal V2.0, Encrypted Drive (IEEE1667)			e (IEEE1667)			

1) 1GB = 1,000,000,000 bytes by IDEMA. A certain portion of capacity may be used for system file and maintenance use, thus the actual available capacity may differ from the labeled capacity.

2) M.2 is the specification of a form factor for ultra-thin PCs. The M.2 standard allows widths of 12, 16, 22 and 30mm and lengths of 16, 26, 30, 38, 42, 69, 80 and 110mm. Commercially popular M.2 are those with a width of 22mm and lengths of 30, 42, 60, 80 and 110mm. Samsung provides the most popular form factor, which is 22mm x 80mm (i.e., 2280), for the convenience of customers.

3) Sequential and random performance measurements are based on IOmeter1.1.0. Performance may vary based on SSD's firmware version, system hardware & configuration. Test system configuration: Intel Core i7-7700K @ 4.2GHz, SAMSUNG DDR4 32GB, OS-Windows 10 Build 10240, Chipset-ASUS PRIME Z270-A.

4) Sequential and random write performance was measured with Intelligent TurboWrite technology being activated. The sequential write performances for the portion of data exceeding over Intelligent TurboWrite buffer size are: 400 MB/s for 250GB, 900 MB/s for 500GB and 1700 MB/s for 1TB. The random write performances for the portion of data exceeding over Intelligent TurboWrite buffer size (tested with QD 32 Thread 4) are: 100,000 IOPS for 250GB, 200,000 IOPS for 500GB and 400,000 IOPS for 1TB. Performance may vary depending on SSD's firmware, system hardware & configuration and other factors.

5) Power consumption is measured with IOmeter1.1.0 version with Intel Core i7-7700K @ 4.2GHz, SAMSUNG DDR4 16GB, Gigabyte GA-Z270X, OS – Windows 10 PRO K x64.

6) All documented endurance test results are in compliance with JESD218 Standards. Please visit www.jedec.org for detailed information on JESD218 Standards

7) TBW means Terabytes Written.

8) Please refer to the detailed warranty statement here at http://www.samsung.com/samsungssd

9) Warranty provides coverage for the stated time period or the TBW, whichever comes first.

Revision 1.0

PRODUCT LINEUP

Density	Model Name	Box Contents	Model Code
250GB*	MZ-V7S250	Samsung SSD 970 EVO Plus 250GB	MZ-V7S250BW
		Warranty Statement	MZ-V7S250B/AM
500GB*	MZ-V7S500	Samsung SSD 970 EVO Plus 500GB	MZ-V7S500BW
		Warranty Statement	MZ-V7S500B/AM
1TB		Samsung SSD 970 EVO Plus 1TB	MZ-V7S1T0BW
(1,000GB*)	MZ-V7S1T0	Warranty Statement	MZ-V7S1T0B/AM

* GB: 1GB = 1,000,000,000 bytes. The actual usable capacity may be less than the labeled capacity.

For more information, including but not limited to the warranty provided for this product, and to download the latest software & manuals, please visit www.samsung.com/ssd and <u>www.samsungssd.com</u>.

Testing Configuration and notes

Below you will find a list of system configurations Samsung used to obtain the results reported in this Data Sheet.

	Read/Write Performance	Power Consumption	
NVMe Interface	PCIe Gen 3.0 x4	PCIe Gen 3.0 x4	
OS	Windows 10 Build 10240	Windows 10 PRO K x64	
CPU	Intel Core i7™ -7700K @ 4.2GHz	Intel Core i7™ -7700K @ 4.2GHz	
Memory	Samsung DDR4 2,400MHz 32GB (16GB x 2ea)	Samsung DDR4 2,133MHz 16GB (8GB x 2ea)	
Chipset	ASUS PRIME Z270-A	Gigabyte GA-Z270X	
Test Program IOmeter 1.1.0 IOmeter 1.1.0		IOmeter 1.1.0	