

Fujitsu recommends Windows 10 Pro.

Data Sheet

FUJITSU Tablet STYLISTIC R727

Unlimited Usability and Productivity with 2 in 1

The FUJITSU Tablet STYLISTIC R727 is a GS certified 2 in1, with a 31.8 cm (12.5-inch) anti-glare display transforming into a full performance and full productivity notebook by simply attaching the strong yet slim magnetic keyboard. Its magnesium-aluminum housing delivers durability for business pros on the move, presenting in tablet mode or working in notebook mode anywhere you like. With the sensitive display you can naturally use a digital pen for notes or signatures on the tablet. Enterprise-grade connectivity like 4G/LTE, manageability and security features like encrypted drives and NFC-based authentication allow you to do your job wherever you want; all in confidence that your data is secure.

Powerful and responsive 2 in 1

Business tablet, business notebook, one device

- Transform a tablet into a full-fledged notebook by simply attaching the magnetic keyboard and unfolding the integrated tablet stand

Mobility first

Smart features for dynamic work styles

- Anti-glare display, durable yet thin & light magnesium-aluminum housing, flexible input options, UC&C capabilities, long runtime of up to 10 hours

Go-anywhere connectivity

Smart features let you do your job wherever you want

- Optional embedded 4G/LTE and NFC

Enterprise-grade manageability and security

Future-proof security features and remote management capabilities keep data safe

- Embedded NFC for contactless SmartCard authentication, encrypted drives, TPM and remote BIOS manageability

Best-in-class office comfort

Switch to a full desktop-like experience in no time

- Cradle to attach peripherals in the office



Components

Operating systems

Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Operating system notes	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle. Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com .	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle. Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com .	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle. Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com .	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle. Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see “FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support” at http://support.ts.fujitsu.com .

*Processor only for retail, SMB, education and government

Hard disk drives (internal)

SSD SATA III, 512 GB, M.2 module, OPAL capable
SSD SATA III, 256 GB, M.2 module, OPAL capable
SSD SATA III, 128 GB, M.2 module, OPAL capable

Hard disk notes

One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
Accessible capacity may vary, also depending on used software.
Up to 20 GB of HDD space is reserved for system recovery
Internal storage interface: M.2 SATA

Interface add on cards/components (optional)

Multimedia

Camera Front camera 2 megapixel, rear camera 5 megapixel with autofocus

Base unit

General system information

Processor	Intel® Core™ i3-7100U processor (2 Cores / 4 Threads, up to 2.3 GHz)	Intel® Core™ i5-7200U processor (2 Cores / 4 Threads, up to 2.8 GHz)	Intel® Core™ i5-7300U processor (2 Cores / 4 Threads, up to 3.0 GHz)	Intel® Core™ i7-7600U processor (2 Cores / 4 Threads, up to 3.4 GHz)
Chipset	Integrated in CPU	Integrated in CPU	Integrated in CPU	Integrated in CPU

General system information

Supported capacity RAM	4 GB	8 GB	8 GB	16 GB
Memory slots	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)
LAN	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219LM	Built-in 10/100/1,000 MBit/s Intel® I219LM
LAN notes	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable
Integrated WLAN	Intel Dual Band Wireless-AC8265			
BIOS version	UEFI Specification 2.5	UEFI Specification 2.5	UEFI Specification 2.5	UEFI Specification 2.5
BIOS features	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios
Audio type	On board	On board	On board	On board
Audio codec	Realtek ALC255	Realtek ALC255	Realtek ALC255	Realtek ALC255
Audio features	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)

Display

Display	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd, 344 cd output with touch and AG	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd, 344 cd output with touch and AG	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd, 344 cd output with touch and AG	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Anti-glare display,1,920 x 1,080 pixel,700:1,400 cd, 344 cd output with touch and AG
Display notes	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.
Sensors	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass
Aspect ratio	16:9	16:9	16:9	16:9
Brightness - typical	400 cd, 344 cd output with touch and AG	400 cd, 344 cd output with touch and AG	400 cd, 344 cd output with touch and AG	400 cd, 344 cd output with touch and AG
Contrast - typical	700:1	700:1	700:1	700:1
Digitizer / Touch Technology	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen	TPK Touch Panel for active pen input plus capacitive 10-finger multi-touch screen
Ambient light sensor	Integrated	Integrated	Integrated	Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight
Viewing angle (h/v) - typical	178°/178°	178°/178°	178°/178°	178°/178°

Graphics

TFT resolution (HDMI)	up to 4,096 × 2,160
TFT resolution (VGA)	1,920 x 1,080 pixel
Max. resolution external display	4,096 x 2,304 pixel
Max. resolution display port	4,096 x 2,304 pixel
Graphics brand name	Intel® HD Graphics 620
Graphics features	3 Display Support (2 external, 1 internal)

Graphics

Graphics notes	Shared memory depending on main memory size and operating system
-----------------------	--

Interfaces

DC-in	1
Audio: line-out / headphone	1 (combo port with Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)
Internal microphones	2 (digital)
USB 3.1 Gen1 (USB 3.0) total	1 (Anytime USB-charge)
VGA	1 (via optional cradle or optional conversion cable)
mini DisplayPort	1
HDMI	1 (via optional cradle or optional DP conversion cable)
Ethernet (RJ-45)	1 (via optional cradle or optional conversion cable)
Memory card slots	1 microSD up to 2GB microSDHC up to 32GB microSDXC up to 128GB Speed Class: up to UHS-I
SIM card slot	1 (MicroSIM - only for models with integrated 4G/LTE)
Interface Module notes	VGA and HDMI via conversion cables (mini DP to VGA and mini DP to HDMI), Ethernet via conversion cable (USB to RJ-45)

Wireless technologies

Antennas	2x dual band for WLAN, 2x for 4G/LTE, Bluetooth shared with WLAN, 1 x NFC
Bluetooth	Bluetooth 4.2 LE
Integrated WLAN	Intel Dual Band Wireless-AC8265
WLAN encryption	WEP, WPA, WPA2
WLAN notes	Import and usage according to country-specific regulations.
Integrated LTE or UMTS	LTE Sierra Wireless EM7305 (Cat. 3) (optional)
LTE/UMTS/GPS notes	Including GPS functionality Import and usage according to country-specific regulations.
NFC	optional
GPS	Embedded in 3G/4G module if configured with WWAN

Power supply

AC adapter	19 V / 65 W (3.42 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
1st battery	Lithium polymer battery 4-cell, 34 Wh
Runtime 1st battery	up to 10h slate only and 9h incl. keyboard (Productivity Workload MobileMark® 2014)
Battery charging time	~ 3h
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.

Dimensions / Weight / Environmental

Dimensions (W x D x H)	319 x 9.5 x 201 mm 12.55 x 0.37 x 7.91 inch
Weight	from 830 g slate only / 1170g incl. keyboard
Weight (lbs)	slate only from 1,83 lbs / incl. keyboard 2,58 lbs
Weight notes	Weight may vary depending on actual configuration (including battery pack)
Operating ambient temperature	Running: 5 - 35 °C; Packed -15 - 60 °C
Operating relative humidity	Running: 20 - 85%; Packed 8 - 85% (relative humidity, non-condensing)
Product	STYLISTIC R727

Germany	GS (planned)
Europe	CE! EN 60950
Global	EPEAT® Gold (dedicated regions) (planned) RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) IT-Eco-Declaration Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Waves MaxxAudio (audio enhancer) LTE / UMTS Connection Manager (if configured with 4G/LTE or 3G/UMTS) Fujitsu Plugfree Network (network management utility) Fujitsu Anytime USB Charge Utility Fujitsu Battery Utility Fujitsu Function Manager Fujitsu DeskUpdate (driver and utility tool) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) CyberLink YouCam (webcam software) Nero (backup and burning software)

Manageability

Manageability technology	PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Supported standards	WMI PXE BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability

Security

System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)			
User Security	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)

Warranty

Warranty period	2 years (for countries within EMEA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Product Related Services - the perfect extension

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://ts.fujitsu.com/Supportservice

Recommended Accessories

Cradle STYLISTIC R series



The cradle for STYLISTIC R series allows you switch from mobile to desktop productivity mode in one click. Enjoy a complete desktop experience with a FUJITSU display, wireless mouse and keyboard or magnetic keyboard and work comfortably on spreadsheets or presentations. Available ports: HDMI, DisplayPort, VGA, 2x USB 3.0, LAN, Audio (1x in / 1x out), DC-In, Kensington lock support.

Order Code:
S26391-F2167-L100

Privacy Filters



To use privacy filters is a must in times of increased safety requirements. Fujitsu's Privacy Filters block unauthorized views on your screen while you are sitting in an external meeting or working in a train. The front view remains clear for the user's eyes only. The filters are easy to attach and what's more: They also protect your screen from small scratches and damages.

Order Code:
S26391-F6098-L212

Privacy Filters



To use privacy filters is a must in times of increased safety requirements. Fujitsu's Privacy Filters block unauthorized views on your screen while you are sitting in an external meeting or working in a train. The front view remains clear for the user's eyes only. The filters are easy to attach and what's more: They also protect your screen from small scratches and damages.

Order Code:
S26391-F6098-L312

Pro Green Case 14



The Pro Green Case 14 protects notebooks with up to 14-inch screens and offers you plenty of style and functionality on your business trips. The front half of the bag has two padded compartments for your power cord and office supplies. The back half of the bag has a divided file compartment for your notebook. Everything will be safe but easily accessible. Its elegant design and recyclable material will impress everyone who sees it.

Order Code:
S26391-F1194-L80

Mini DisplayPort to DP1.4 Cable



The FUJITSU Mini DisplayPort to DP1.4 Cable connects your system with your display offering you an ultra high resolution graphics connection.

Order Code:
S26391-F6055-L221

Active Pen for STYLISTIC R726



Annotate and fill in forms on your tablet with the premium, real size FUJITSU Active Pen. Navigate, erase and right-click with the function button. Includes a battery and a pen holder to attach to the keyboard or tablet.

Order Code:
S26391-F2169-L100

VGA Conversion Adapter (Mini Display Port to VGA)



Connect and present on demand from your STYLISTIC Tablet with the FUJITSU VGA Conversion Cable. From the mini Display Port on your Tablet to the VGA port on the projector or display. (Picture similar to product)

Order Code:
S26391-F2169-L200

HDMI Conversion Adapter (mini DP to HDMI)



The FUJITSU HDMI Conversion Cable lets you connect your STYLISTIC tablet to projectors and screens that have a modern HDMI interface. (Picture similar to product)

Order Code:
S26391-F2169-L300

LAN Conversion Cable (USB to LAN)



The FUJITSU LAN Conversion Cable allows you to connect your STYLISTIC tablet to a wired network connection. (Picture similar to product)

Order Code:
S26391-F2169-L400

Display B24-9 TS



The FUJITSU Display B24-9 TS is a widescreen display with 1920 x 1080 Full HD resolution with a ultra-thin bezel housing. The monitor has a wide viewing angle that delivers consistent picture quality and DisplayView™ Click manageability software for further enhancing monitor features with a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:
S26361-K1643-V160

**Magnetic Keyboard STYLISTIC
R726**

The Magnetic Keyboard for the STYLISTIC R726 empowers you to easily switch between tablet and notebook mode. Its magnetic connection makes it easy to attach or detach it from the tablet so you can transform the device the way you want and need it for your individual workstyle.

S26391-F2114-L**
(**country specific version)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Tablet STYLISTIC R727, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Tablet STYLISTIC R727, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/tabletpc

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2019-01-18 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright 2019 Fujitsu Technology Solutions GmbH