



Highlights

Fast Mobile Broadband for All Your Devices

Share your high-speed mobile broadband connection with multiple Wi-Fi devices such as smartphones, tablets, PCs, and more at blazing fast speeds.

Ease of Use

Create a wireless network with the touch of a button where needed. Wi-Fi Protected Setup (WPS) means no need to worry about passwords and SSIDs.

Go Anywhere

Small enough to fit in your pocket and long-lasting battery allows you to create a private Wi-Fi hotspot wherever you are.



DWR-933

4G/LTE Cat 6 Wi-Fi Hotspot

Features

Connectivity

- Download speeds of up to 300 Mbps with Cat 6 LTE-A
- Create a wireless hotspot to share your mobile broadband connection with up to 10 devices.
- Uses a SIM card to connect to the Internet
- Dual-band Wi-Fi with combined speeds of up to 1,200 Mbps
- Can connect to a PC via USB to add Internet connectivity

Portability

- Up to 14 hours battery life, so you stay connected longer
- Small size lets you slip it into a purse or pocket and take it wherever you go

Security

- WPA/WPA2 Wi-Fi encryption
- Built-in firewall
- Wi-Fi Protected Setup (WPS) for one-touch connection with other devices

The 4G/LTE Cat 6 Wi-Fi Hotspot is a high-speed portable mobile Wi-Fi hotspot. It allows you to share a single mobile Internet connection with up to 10 Wi-Fi devices, over 2 dedicated Wi-Fi bands with combined speeds of up to 1,200 Mbps. The compact size and the long-lasting, rechargeable battery means you can create a private Wi-Fi hotspot wherever you are.

The DWR-933 supports Cat (Category) 6 LTE to give blazing-fast download speeds of up to 300 Mbps. It lets you take full advantage of your operator's 4G network while sharing your connection with others. Send large e-mails in a cafe while your friend streams their favourite shows, or share your connection at the airport so you and your colleagues can video conference with customers while waiting for your flight.

Technical Specifications

General

Frequency Support ¹	<ul style="list-style-type: none"> Category 6: FDD-LTE: Band 1/3/7/8/20, TDD-LTE: Band 38 CA: 1A+3A, 1A+7A, 1A+8A, 1A+20A, 3A+3A, 3C, 3A+7A, 3A+8A, 3A+20A, 3A+38A, 7A+7A, 7C, 7A+20A, 38C 	<ul style="list-style-type: none"> UMTS/HSPA+/DC-HSPA+: 850/900/1900/2100 MHz GSM:850/900/1800/1900 MHz
Data Throughput ²	<ul style="list-style-type: none"> LTE Mode: <ul style="list-style-type: none"> Downlink: 300 Mbps Uplink: 50 Mbps 	<ul style="list-style-type: none"> WCDMA/HSPA/HSPA+/DC-HSPA Mode: <ul style="list-style-type: none"> Downlink: 42 Mbps Uplink: 5.76 Mbps
Wi-Fi Standards	<ul style="list-style-type: none"> 802.11ac 802.11n 	<ul style="list-style-type: none"> 802.11g 802.11b
Wi-Fi Data Rates ²	<ul style="list-style-type: none"> Up to 867 Mbps in 802.11ac (2x2) mode Up to 300 Mbps in 802.11n (2x2) mode 	<ul style="list-style-type: none"> Up to 54 Mbps in 802.11g mode Up to 11 Mbps in 802.11b mode
Wi-Fi Encryption	<ul style="list-style-type: none"> WPA/WPA2 64/128-bit WEP 	<ul style="list-style-type: none"> WPS Push-Button Connection
Advanced Functions	<ul style="list-style-type: none"> Built-in firewall Built-in NAT Port range forwarding 	<ul style="list-style-type: none"> DMZ UPnP

Physical

Interfaces	<ul style="list-style-type: none"> 802.11ac/n/g/b wireless LAN Standard 6 pin micro-SIM/USIM card interface 	<ul style="list-style-type: none"> Micro-USB port for charging and virtual network port microSD card slot (up to 64 GB)
Display	<ul style="list-style-type: none"> 0.96 inch OLED display, 128 x 64 pixels 	
Display Information	<ul style="list-style-type: none"> Network type Signal strength Roaming status SMS & SMS status Internet connection status 	<ul style="list-style-type: none"> Carrier Battery status Wi-Fi & security status Wi-Fi clients
Power	<ul style="list-style-type: none"> DC 5 V / 1 A 	<ul style="list-style-type: none"> 3000 mAh Li-ion battery
Dimensions	<ul style="list-style-type: none"> 98 x 71 x 18.8 mm 	
Weight	<ul style="list-style-type: none"> 120 g 	
Operating Temperature	<ul style="list-style-type: none"> 0 to 40 °C (32 to 104 °F) 	
Storage Temperature	<ul style="list-style-type: none"> -20 to 70 °C (-4 to 158 °F) 	
Operating Humidity	<ul style="list-style-type: none"> 10% to 90% (non-condensing) 	
Certifications	<ul style="list-style-type: none"> BSMI 	<ul style="list-style-type: none"> RoHS

¹ Supported frequency band is dependent upon regional hardware version.

² Data rates are theoretical. Data transfer rate depends on network capacity and signal strength.



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., First Floor, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2020 D-Link Corporation. All rights reserved. E&OE.

Updated January 2020

D-Link®