



## Info generali

### Interno - Lampade da parete

Indoor wall mounted adjustable lamp with multiple sources, in-built switch and diffuse and direct light emission

|               |                         |
|---------------|-------------------------|
| Ean           | 8021696103204           |
| Articolo      | HOTEL AP2 CANVAS        |
| Installazione | Lampade da parete       |
| Garanzia      | 5 years                 |
| Peso lordo    | 2.02 kg                 |
| Volume        | 0.016576 m <sup>3</sup> |

## Info tecniche e installative

|                           |                                                                                |
|---------------------------|--------------------------------------------------------------------------------|
| Peso netto                | 1.41 kg                                                                        |
| Classe di isolamento      | I                                                                              |
| Grado di protezione       | IP20                                                                           |
| Conformità                | CE                                                                             |
| Temperatura d'esercizio   | 0° ~ +40 °C                                                                    |
| Efficienza a pieno carico | X                                                                              |
| Dimmer                    | NO, On-Off                                                                     |
| Alimentazione             | 100-240 V AC 50/60 Hz<br>Integrated switch button                              |
| Alimentatore              | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |
| Orientabilità             | YES                                                                            |

## Info sorgente e prestazionali

|                       |                                                  |
|-----------------------|--------------------------------------------------|
| Sorgente integrata    | Light bulb (not included), Integrated LED module |
| Sorgente sostituibile | Replaceable (LED: by qualified operators only)   |
| Potenza               | E27/LED max 1 x 60W / 1.5 W                      |
| Emissione             | Diffuse + Direct                                 |
| Consumo massimo       | max 60W / LED 1.5 W                              |
| Caratteristiche LED   | LED SMD BRIDGELUX                                |
| CCT LED               | 3000 K                                           |
| Durata LED (t. 25°c)  | 20000 h                                          |
| CRI                   | > 80                                             |
| Fascio luminoso       | 23°                                              |
| Flusso sorgente       | 55 lm                                            |
| Flusso utile          | LED 45 lm                                        |
| Rischio fotobiologico | 2                                                |
| Lampadina inclusa     | 1 - E14 OLIVA 4W 3000K CRI80 SATIN               |