



Info generali

Tecnico - Lampade da incasso

Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission

Ean	8021696208596
Articolo	DYNAMIC SOURCE 15W 4000K
Installazione	Recessed (Ceiling)
Garanzia	5 years
Peso lordo	0.36 kg
Volume	0.003044 m ³

Info tecniche e installative

Peso netto	0.35 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	Separate, included Replaceable (by qualified operators only), electronic
Protezione frontale	IP54
Accessori non inclusi	Frame, Reflector, Narrow or wide beam lens, additional optic (Honeycomb or Elliptical), Dimmable driver

Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	15 W
Emissione	Direct
Consumo massimo	max 15 W
Caratteristiche LED	LED COB
CCT LED	4000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	35°
Flusso sorgente	1650 lm
Flusso utile	1350 lm
Potenza in stand-by	< 0.50 W