

Info generali

Tecnico - Lampade da incasso


Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission



Ean	8021696252995
Articolo	DYNAMIC SOURCE 09W 4000K
Installazione	Recessed (Ceiling)
Garanzia	5 years
Peso lordo	0.35 kg
Volume	0.003044 m ³

Info tecniche e installative

Peso netto	0.18 kg
Classe di isolamento	II
Grado di protezione	IP20
Conformità	CE
Temperatura d'esercizio	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Alimentazione	220-240 V AC 50/60 Hz
Alimentatore	Separate, included Replaceable (by qualified operators only), electronic, tridonic
Protezione frontale	IP54
Accessori non inclusi	Frame, Reflector, Narrow or wide beam lens, additional optic (Honeycomb or Elliptical), Dimmable driver



Info sorgente e prestazionali

Sorgente integrata	Integrated LED module
Sorgente sostituibile	Replaceable (by qualified operators only)
Potenza	9 W
Emissione	Direct
Consumo massimo	max 9 W
Caratteristiche LED	LED COB
CCT LED	4000 K
Durata LED (t. 25°C)	50000 h
CRI	> 90
SDCM	3
Fascio luminoso	35°
Flusso sorgente	1000 lm
Flusso utile	840 lm
Potenza in stand-by	< 0.50 W