

## Info generali

## Tecnico - Lampade da incasso


Indoor ceiling recessed projector with integrated LED sources, enhanced protection and direct light emission



|               |                          |
|---------------|--------------------------|
| Ean           | 8021696252971            |
| Articolo      | DYNAMIC SOURCE 09W 2700K |
| Installazione | Recessed (Ceiling)       |
| Garanzia      | 5 years                  |
| Peso lordo    | 0.35 kg                  |
| Volume        | 0.003044 m <sup>3</sup>  |

## Info tecniche e installative

|                         |                                                                                                               |
|-------------------------|---------------------------------------------------------------------------------------------------------------|
| Peso netto              | 0.18 kg                                                                                                       |
| Classe di isolamento    | II                                                                                                            |
| Grado di protezione     | IP20                                                                                                          |
| Conformità              | CE                                                                                                            |
| Temperatura d'esercizio | 0° ~ +40 °C                                                                                                   |
| Dimmer                  | Non-dimmable, On-Off                                                                                          |
| Alimentazione           | 220-240 V AC 50/60 Hz                                                                                         |
| Alimentatore            | Separate, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic                      |
| Protezione frontale     | IP54                                                                                                          |
| Accessori non inclusi   | Frame, Reflector, Narrow or wide beam lens,<br>additional optic (Honeycomb or Elliptical),<br>Dimmable driver |



## Info sorgente e prestazionali

|                       |                                           |
|-----------------------|-------------------------------------------|
| Sorgente integrata    | Integrated LED module                     |
| Sorgente sostituibile | Replaceable (by qualified operators only) |
| Potenza               | 9 W                                       |
| Emissione             | Direct                                    |
| Consumo massimo       | max 9 W                                   |
| Caratteristiche LED   | LED COB                                   |
| CCT LED               | 2700 K                                    |
| Durata LED (t. 25°C)  | 50000 h                                   |
| CRI                   | > 90                                      |
| SDCM                  | 3                                         |
| Fascio luminoso       | 35°                                       |
| Flusso sorgente       | 840 lm                                    |
| Flusso utile          | 770 lm                                    |
| Potenza in stand-by   | < 0.50 W                                  |