



# PRELIMINARY PRODUCT INFORMATION

SPECIFICATIONS AND IMAGES SUBJECT TO CHANGE.



## T-Sub-AX15B

You can never have enough... **BASS!**



**700w**  
Continuous

### Everyone loves bass !

That is exactly why we have created the T-Sub-AX15B - our all-new 700w Continuous, 1400w Peak 15" active subwoofer.

The internal Class D amplifier delivers huge output power into the custom quad-layer 15" Wharfedale Pro LF driver to produce extreme subs and low end pressure into any system.

Built for big bass, the plywood constructed cabinet is rock solid and is protected in durable Rhino Rock paint.

You'll not only 'feel' the T-Sub-AX15B, but you will also see it! A new illuminated WP logo badge subtly glows and adds to the overall on-stage "power" of the new T-Sub.

T-Sub-AX15B is the perfect companion for a Typhon or a Titan active loudspeaker. It also has 75% more power than the current Titan Sub-A15 MKII.

### Hold on to your socks!

**T-Sub-AX15B is going to blow them off!**

**129dB**  
Max SPL @1m



FOR TYPHON AND TITAN

3.0" VOICE COIL - QUAD LAYER DRIVER

### WHAT MAKES IT GREAT?

- ✓ 700w Continuous (1400w peak)
- ✓ 3.0" voice coil - Quad layer driver
- ✓ Plywood construction
- ✓ Illuminated LED front logo badge
- ✓ Convection cooled Class D amplifier
- ✓ Adjustable low pass filter
- ✓ 35mm pole socket & durable side handles

### WHEN IS IT AVAILABLE?

Shipping from : **AUGUST 2020**



# PRELIMINARY PRODUCT INFORMATION

SPECIFICATIONS AND IMAGES SUBJECT TO CHANGE.

## T-Sub-AX15B



**+75%**  
power over  
Titan Sub A15 MKII

**700w Continuous** **1400w PEAK**



**1**  
T-Sub with  
**TITAN**



**2**  
T-Sub with  
**TYPHON**

# SPECIFICATIONS



|   |                                |
|---|--------------------------------|
| <b>Model Name</b>                       | <b>T-Sub-AX15B</b>             |
| System Type                             | Active 15" Subwoofer           |
| Frequency Response (+/-3dB)             | 45Hz-200Hz                     |
| Sensitivity @ 1W / 1m)                  | 97dB                           |
| Maximum SPL (peak@1m)                   | 129dB                          |
| <b>Low Frequency Transducer</b>         |                                |
| Size (mm / inches)                      | 404mm / 15"                    |
| Coil Size (mm / inches)                 | Quad layer 3.0"                |
| Impedance                               | 4Ω                             |
| <b>Amplifier</b>                        |                                |
| Low-Frequency Power Amplifier (Class D) | 700w Continuous / 1400w Peak   |
| Crossover Frequency                     | LPF 80-200Hz (adjustable)      |
| <b>Controls</b>                         |                                |
| Amplifier Protection                    | Yes                            |
| Power On Protection                     | Power switch on / off mute     |
| Thermal Protection                      | Amplifier shutdown, auto reset |
| Driver Protection                       | Yes                            |
| DC Protection                           | Yes                            |
| Short Protection                        | Yes                            |
| Limiter Indicator                       | Red LED                        |
| Input type                              | Balanced                       |
| Input Connector                         | Female XLR                     |
| Input Impedance                         | 47KΩ Balanced                  |
| Maximum Input Level                     | 5V                             |
| Input Sensitivity                       | -10dB                          |
| Input Connectors                        | Female XLR                     |
| Line Output Connector                   | Male XLR                       |
| Phase Switch Selection                  | 0° / 180°                      |
| <b>AC Power details</b>                 |                                |
| Power Supply                            | SMPS                           |
| AC Power Options                        | 100V-120V and 200V-240V        |
| Power Indicator                         | Green(back) / Blue logo(front) |
| <b>Enclosure</b>                        |                                |
| Enclosure Material                      | 15mm Plywood                   |
| Colour                                  | Black                          |
| Grille                                  | 1.5mm steel                    |
| Pole Mount(Top)                         | 35mm                           |
| <b>Dimensions (Unpacked):</b>           |                                |
| Height                                  | 591mm / 23.27"                 |
| Width                                   | 454mm / 17.9"                  |
| Depth                                   | 523.9mm / 20.63"               |
| <b>Dimensions (packed):</b>             |                                |
| Height                                  | 689mm / 27.1"                  |
| Width                                   | 544mm / 21.4"                  |
| Depth                                   | 610mm / 24.0"                  |
| Weight                                  |                                |
| Net Weight (kg / lbs)                   | 25.7kg / 56.5lbs               |
| Gross Weight (kg / lbs)                 | 29.5kg / 64.9lbs               |

