



Acqua fredda
Cold water



Per uso saltuario
For occasional usage



Attacco
connessione rapida
Quick connection



Lancia getto rotante
Rotary lance

TSS®
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Carrello a 2 ruote completo di manico
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa in alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Sistema di arresto totale dell'idropulitrice a distanza
- Protezione termica del motore
- Dispositivo click-fast
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m
- Two-wheel trolley with handle
- 3 Axial stainless steel pistons wobble-plate pump with aluminium head
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Remote control for total shut-down of high pressure washer
- Motor thermal protector
- Click-fast connection device
- Inspectable water filter
- Electric cable length 5 m

Fornito con - Equipped with:



Pistola con attacco rapido
Trigger gun w/quick connection
(3082283)

(0,5 l)



Kit schiumogeno con serbatoio
Foam lance bottle
(3480200)



Prolunga lancia
Lance extension
(4100771)



Testina getto regolabile
Adjustable jet nozzle
(3980110)



Tubo AP 5 m
HP hose 5 m
(3500350)



Testina getto rotante
Rotary jet nozzle
(4100800)

ø 12 cm



Portatile
Portable



Battistrada in gomma
Rubber wheels



Porta accessori
Built-in accessories holder



Filtro acqua ispezionabile
Inspectable water filter



Dati Tecnici / Technical Data

MOD	COD	MAX								
		bar	psi	l/h	gph	kW	rpm	Hz	V	kg
143	13690	120	1740	390	103	1,5	3400	1~50-60	220-240	5

Temperatura massima acqua / Max inlet water temperature
50°C 122°F IPX5-S1