ThinkVision T24d-10 MONITOR

PROFESSIONAL PERFORMANCE AT WIDE-VIEW DISPLAY.



A SLEEK 24" MONITOR WITH OUTSTANDING IMAGE OUALITY.

The sleek, stylish ThinkVision T24d-10 Monitor doesn't just display images – it presents them at over 99% sRGB color gamut and exceptionally crisp 1920 x 1200 resolutions cross near-frameless 24" display. Enjoy vivid images across wide (178°/178°) viewing angles with no color distortion or reflection. With elegant slim design, the monitor fit in any workspace. Get the large visual workspace you need with a professional monitor designed to enhance productivity and make collaboration easy.

WHY YOU SHOULD BUY THE THINKVISION T24d-10 MONITOR



Performance and Productivity

Professional performance defines the WUXGA (1920 x 1200) resolution, over 99% sRGB high color gamut, 1000:1 contrast and In-Plane Switching for exceptional viewing angles across the entire 24" display.



Productivity at its Finest

A full-function stand ensures your display sports an executive look regardless of whether you swivel, tilt, pivot, or lift. Paired with near-edgeless screen, you can enjoy a clean look and seamless views cross multi-monitor displays.



Ergonomic and Manageable

The ergonomic full-function stand is perfect for collaboration. It supports the new tiny clamp bracket for easy set-up of the ThinkCentre Tiny. Practical cable management effectively manages desktop clutter.

THE THINKVISION T24d-10 MONITOR IS BEST SUITED FOR



Users and businesses that need a highest-quality professional monitor.



Organizations that require highly detailed display for uses like finance or graphics.



Organizations that require professional quality monitors that also deliver a green advantage.

















ThinkVision T24d-10 MONITOR

SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size Panel Type Resolution Backlight Aspect Ratio Pixel Pitch (W x H) (mm) Dot/Pixel Per Inch (DPI/PPI) Anti-Glare Screen Dimensions (W x H) (mm) (inches) Maximum Brightness (Typical) Viewing Angle (H/V at CR 10:1) Contrast Ratio (Typical) Dynamic Contrast Ratio Color Gamut (CIE 1931) Display Colors (Typical) Response Time Extreme Typical Off	24" In-Plane Switching 1920 x 1200 WLED 16:10 0.27 x 0.27 94 PPI Yes 518.4 x 324 20.41" x 12.75" 300 cd/m² 178°/178° 1000:1 3M:1 99% sRGB 16.7 Million 4 ms 7 ms 15 ms	Size Packed (mm) (inches) Size Unpacked with Stand (mm) (inches) Size Monitor Head Only (mm) (inches) Distance from Table to Panel Lowest Pixel at Bottom of Screen (mm / inches) Highest Pixel at Top of Screen (mm / inches) Stand Base Footprint Area (mm) (inches) Weight Packed Unpacked Monitor Head Only	160 x 655 x 422 6.3" x 25.79" x 16.61" 533.2 x 260.4 x 497.4 20.99" x 10.25" x 19.58" 533.2 x 42.3 x 355.1 20.99" x 1.67" x 13.98" 56 / 2.2" 490 / 19.29" 250 x 250 9.84" x 9.84" Starting at 19.18 lbs (8.7 kg) Starting at 12.41 lbs (5.63 kg) Starting at 8.77 lbs (3.98 kg)
SIGNAL INPUT		POWER CONSUMPTION	

SIGNAL INPUT

Video Input Signals Video Cables Supplied Video Cable Length USB Hub USB Cable Supplied	VGA + DisplayPort 1.2 + HDMI 1.4 VGA + DisplayPort + HDMI 1.8 m USB 3.01 Yes
Audio-Out	Yes (3.5 mm)

SIGNAL INTERFACE / PERFORMANCE

Horizontal Frequency	30 kHz - 83 KHz
Vertical Frequency	50 Hz - 75 Hz
Native Resolution	1920 x 1200
Maximum Pixel Clock Speed/ Bandwidth	
VGA	205 MHz
HDMI™	165 MHz
DisplayPort™	165 MHz
Default Color Temperature	6500 K
Preset Display Modes	20
OSD Buttons	5
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian

MECHANICAL

^{*} NA only.

Typical	22 W
Maximum	64 W
Sleep-Mode	<0.3 W
Switch Off-Mode	<0.3 W
Power Supply	Internal
Power Voltage	100 VAC - 240 VAC
Voltage Dynamic Frequency	50 Hz – 60 Hz

ENVIRONMENTAL

iemperature	
Operating	0°C – 40°C
Non-Operating	-20°C – 60°C
Humidity	
Operating	10% - 80%
Non-Operating	5% – 95%
Altitude	
Operating	0 m – 5000 m
Non-Operating	0 ft - 40,000 ft
Arsenic-Free Glass	Yes
PVC-Free	Yes
Mercury-Free	Yes
PCC % of Plastic Resins	>85%

COMPLIANCE

EPEAT	Gold
ENERGY STAR Rating	8.0
ULE	Gold
TCO	TCO Display 7.0 / TCO Edge 2.0
RoHS (EU 2002/95/EC)	Yes
China Energy Efficiency Standard	Tier 2
Windows Certification	Windows 7 / Windows 10

WARRANTY AND AVAILABILITY

3 Years Warranty Geography Availability WW





WWW.LENOVO.COM

Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.