

Eaton 5P1150IRNG2

Catalog Number: 5P1150IRNG2

Eaton 5P UPS, 1150 VA, 920 W, Input: C14, Outputs: (6) C13, Rack, 1U, Network card

General specifications

Product Name	Catalog Number
Eaton 5P Gen2 UPS	5P1150IRNG2
EAN	Product Length/Depth
3553340710407	509 mm
Product Height	Product Width
43.2 mm	438 mm
Product Weight	Warranty
14.2 kg	3 year on electronics, 2 year on battery
Compliances	Certifications
LVD Directive (CB)	IEC/EN 62040-1
EMC Directive	IEC/EN 62040-2
RoHS Directive	IEC/EN 62040-3
WEEE Directive	UL 1778
Packaging Directive	CSA-C22.2
Batteries Directive	CE
	UKCA
	Cm
	Ukr
	KCC
	cTUVus
	BIS

Special features

Automatic Voltage
Regulation (AVR)
High-density protection for
networks: 1U only
Energy efficient, reduce
energy and cooling costs
Delivers clean sinewave
output
1 slot for optional com card
(Network management card,
Relay card or Network and
Industrial card)
Compatible with Virtual
environments (VMware,
Hyper-V, Citrix Xen, Redhat)
Fully integrates with Eaton
Brightlayer Software suite
1 USB port + 1 serial port
Advanced Battery
Management (ABM+)
technology to increase
battery lifetime and improve
life time prediction accuracy
Next-generation graphical
LCD display
Hot swappable batteries
Remote reboot and runtime
optimization thanks to 2
manageable outlet groups
Network card included

Type

UPS

Topology

Line-interactive

Form factor

Rack

Rack size

1U

Construction type

482.6 mm (19 inch) device

Color

Black/silver

Enclosure

Black/silver

VA rating

1150 VA

Wattage

920 W

Rack mounting kit

Yes

Package contents

Rack-mounting kit
Cable locking system
USB cable
(2) IEC-IEC cables
Quickstart guide
Safety instructions
Network card

Auto shutdown function

Yes

Primary frequency - max

70 Hz

Primary frequency - min

47 Hz

Input connection

C14

Input nominal voltage

230V default (200/208/220/230/240V)

Nominal frequency

50-60 Hz

Input frequency range

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40 Hz in
low sensitivity mode

Receptacle

(6) C13

Number of Outputs C13

6

Output waveform

Sine wave

Voltage

230V

Output nominal voltage

230V default (200/208/220/230/240V)

Feed type

1

Voltage type

AC

Runtime graph

View runtime graph

Battery management

ABM or constant voltage charging method (user selectable),
automatic battery test, deep discharge protection

Battery replacement

User replaceable

Battery rating

6 V / 9 Ah

Battery type

Lead-acid maintenance-free (replaceable)

Extended battery capability

No

Runtime at half load

12.5 min

Communication

USB port (HID compliant)
Serial port (RS232)
Mini-terminal block for
remote On/Off and Remote
Power Off
Dry contacts (2 outputs,
optocoupler, RJ)

Expansion slots

One slot for optional communication card

Ethernet interface

Yes

Includes network card

Yes

Software compatibility

Eaton Brightlayer Software suite

User interface

Multilingual graphical LCD display

Type of interface

Other

Potential free switch contact

Yes

Altitude

3000 m

BTU Rating

Online: 63, Battery: 465 BTU/hr

Noise level

<35 dB at 1 meter

Relative humidity

0-90% non-condensing

Temperature range

0-90% non-condensing

Input voltage - max

294 V

Input voltage - min

150 V

Output voltage - max

240 V

Output voltage - min

200 V

Secondary frequency - max

60 Hz

Secondary frequency - min

50 Hz

Battery quantity

4

Efficiency

98,2

Input voltage range

160-294 V (adjustable to 150 V-294 V)

Output frequency

50/60 Hz

Output power factor

0,8

Output voltage range

230 V (+6%/-10%)

Phase (input)

1

Phase (output)

1

Runtime at full load

3



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia