

MIG 140

NEW



TECHNICAL SPECIFICATIONS	MIG 140	
Main Voltage - Tension de réseau - Voltaje de red - Tensão de rede Tensione di rete - Netzwerkspannung - Сетевое напряжение	230V, 50-60Hz	
Absorbed Power - Puissance absorbée - Potencia absorbida - Potência absorvida Potenza assorbita - Absorbierte Kraft - поглощенная мощность (MAX)	kVA MIG 4,3 TIG 2,4	kW MIG 3,3 TIG 1,7
No load Voltage - Tension à vide - Tensión en vacío - Tensão de vácuo Tensione a vuoto - Vakuumspannung - Вакуумное напряжение	56V	
Welding Current - Courant de soudage - Corriente de soldadura - Corrente de soldagem Corrente di saldatura - Schweißstrom - Сварочный ток	MIG 20-130 MMA 20-100 TIG 20-100	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho Fattore di servizio - Einschaltdauer - Соотношение прерывистости - EN 60974-1	MIG 30/130 MMA 30-100 TIG 30-100	
Duty Cycle - Cycle de service - Ciclo de trabajo - Ciclo de Trabalho Fattore di servizio - Einschaltdauer - Соотношение прерывистости - 20°	130A@90%	
Box volume - Volume de la boîte - Volumen caja de carton - Volume caixa de cartão Volume scatola - Kartonschachtel Volumen - Объем коробки	0,028m³	
Box Size - Taille de la boîte - Dimensiones caja de carton - Dimensões caixa de cartão Dimensione scatola - Kartonschachtelgröße - Размер коробки (LxWxH)	375x330x230mm	
Box Weight - Poids de la boîte - Peso caja de carton - Peso caixa de cartão Peso scatola - Kartonschachtel Gewicht - Вес коробки	9,2 Kg	
PCS per Masterbox - PCS par Masterbox - PCS por Masterbox - PCS por Masterbox Pezzi per masterbox - Stücke für die Masterbox - количество для мастер-боксы	1 PCS	
PCS per Euro Pallet - PCS par Euro Pallet - PCS por Euro Pallet - PCS por Euro Pallet Pezzi per Europalette - Stücke für die Europalette - Пьесы для европоддонов	50 PCS	
Code - Code - Código - Code - Codice - Code - код	58859	
Bar Code - Code barre - Código barra - Code à barres Codice a barre - Bestellcode - EAN	8004386588598	

WIRE

SG2 Ø0,6-1,0 mm
INOX Ø0,6-1,0 mm
FLUX Ø0,8-Ø0,9 mm



Ø100 and with
REEL BRACKET
200mm



FLUX 0,9 mm
Ø100 mm



6,5 KVA