

1500 VA UPS con LCD

EG-UPS-036

ULTIMATE DEFENCE

- Informative LCD display
- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Caratteristiche

- Regolazione automatica del voltaggio in output (AVR)
- Interfaccia USB
- Indicatori status del LCD
- Protezione da corto circuiti
- Protezione da sovraccarichi e fulmini
- Allarmi sonori e visivi
- Protezione da sovraccaricamento e sovrascaricamento

Confezione

Quantità per cartone, pezzi	1
Volume del cartone, CUM	0.0396
Peso del cartone, Kg	20.82
Individual package size LxWxH:	500x300x150 mm
Carton size LxWxH:	550x240x300 mm
Paese di origine	CN
Barcode	8716309124744
Customs code	8504408590

Contenuto della Confezione

UPS
Power cord
USB cable
Software CD
Spare fuse

Certificazioni



Specifiche

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$ (162-295V), 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 10\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 8...20 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7 Ah x 4 pcs

Charge time: up to 90% after 6-8 hours

Sockets: 1 x C14 input, 3 pcs x C13 output, 3 pcs x german Shuko output

Interface communication: USB-BF socket, RJ45

Operating conditions: 0°C ~ 40°C, at humidity 20 ~ 90 %RH non condensing

Power: 3000 VA (1800 W)

Charging current: up to 1.2 A

Noise: < 45 dB at 1 m distance

Dimensions: 157.5 x 452 x 211 mm

Net weight: 19.3 kg

"Cold-start" function

Requisiti di sistema

Software is compatible with Windows 7/8/10/11, Windows 2008 server

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a