



La foto è a scopo illustrativo



Eaton 3P1700UD

Eaton 3P Ellipse UPS USB DIN, 1700 VA, 1040 W, Input: C14, Outputs: (4) Schuko, (4) Schuko surge only, USB charge, Tower

General specifications

PRODUCT NAME	Eaton 3P Ellipse UPS
CATALOG NUMBER	3P1700UD
EAN	3553340621437
PRODUCT LENGTH/DEPTH	312 mm
PRODUCT HEIGHT	305 mm
PRODUCT WIDTH	81 mm
PRODUCT WEIGHT	7.8 kg
WARRANTY	3 year on electronics, 2 year on battery
COMPLIANCES	CE Marked LVD Directive (CB) EMC Directive RoHS Directive WEEE Directive Packaging Directive Batteries Directive IEC 61643-11
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 CE UKCA Cm
MODEL CODE	Eaton 3P Ellipse 1700 USB DIN

Batteria	
BATTERY TYPE	Sealed, lead-acid
RUNTIME GRAPH	View runtime graph
BATTERY QUANTITY	2
BATTERY MANAGEMENT	Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable
BATTERY RATING	12 V / 9 Ah
EXTENDED BATTERY CAPABILITY	No

Collegamento in ingresso	
INPUT CONNECTION	C14
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
NOMINAL FREQUENCY	50-60 Hz
INPUT CORD LENGTH	1.5 m
INPUT VOLTAGE RANGE	184-264 V (adjustable to 161-284 V)
INPUT FREQUENCY RANGE	46-70 Hz

Dati ambientali	
ALTITUDE	3000 m
NOISE LEVEL	<25 dB at 1 meter
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
RELATIVE HUMIDITY	0 - 95 % (non-condensing)

Collegamento in uscita	
RECEPTACLE	(4) Schuko, (4) Schuko surge only
VOLTAGE	230V
WATTAGE	1040W
OUTPUT POWER FACTOR	0.6
OUTPUT VOLTAGE RANGE	184-264 V (adjustable to 161-284 V)
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
FEED TYPE	1
TOPOLOGY	Offline
VA RATING	1700VA

Comunicazioni	
INCLUDES NETWORK CARD	No
COMMUNICATION	USB port (HID compliant)
ETHERNET INTERFACE	No
USER INTERFACE	LED display
POTENTIAL FREE SWITCH CONTACT	No
EXPANSION SLOTS	Yes
SOFTWARE COMPATIBILITY	Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)
TYPE OF INTERFACE	USB

Caratteristiche aggiuntive	
USB INTERFACE	Yes
CONSTRUCTION TYPE	Free standing model
PACKAGE CONTENTS	• Input cable • USB cable • Quick start • Safety instructions
PHASE (OUTPUT)	1
AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
EFFICIENCY	97
RACK MOUNTING KIT	No
PHASE (INPUT)	1
SURGE PROTECTION	Yes

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATA:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublino 4, Irlanda
Eaton.com

Follow us on social media to get the latest product and support information.

