Specifications

Product	Name	NAVEE Electric Scooter
	Model	V40i-U
Dimensions	Vehicle: L × W × H[1]	44.9 × 22.5 × 46.8 in (1140 × 571 × 1189 mm)
	After Folding: L × W × H	44.9 × 22.5 × 19.3 in (1140 × 571 × 490 mm)
Net Weight	Vehicle Net Weight	39 lbs (17.7 kg)
Rider	Load Range	55.1 - 264.6 lbs (25-120 kg)
	Age (years)	16-50 years
	Body Length	3'11"-6'6"(120-200 cm)
Assembled Electric Scooter	Max. Speed	20 mph (32 km/h)
	General Range[2]	Approx. 25 miles (40 km)
	Max. Climbing Angle	Approx. 18%
	Suitable Surfaces	Cement or asphalt road, with benches of less than 1 cm or crevices narrower than 3 cm
	Operating Temperature	14-104 ° F (-10 to 40 °C)
	Storage Temperature	-4-113 ° F (-20 to 45 °C)
	IP Rating	IPX5
	Charging Time	Approx. 6 h
Battery Pack	Model	T2208-BA3A
	Nominal Voltage	36 VDC
	Max. Charge Voltage	42 VDC
	Rated Energy	275.4 Wh
	Intelligent Battery Management System	Over-heating, short circuit, over-current, over-discharge, and over-charge protection
	Normal Charging Temperature Range	32-104 ° F (0 to 40 °C)
	Rated Capacity	7.65 Ah
Wheel Motor	Rated Power	350 W (0.35 kW)
Battery Charger	Model[3]	LI-0554200130NA
	Output Power	53.3 W (0.0533 kW)
	Input	100-240 V~ 50/60 Hz
	Max. Output Voltage	42.0 VDC
	Rated Output	41.0 VDC, 1.3 A
Tire	Front & Back Tires	10-inch Pneumatic Tires
Bluetooth	Frequency Band	2.4000 - 2.4835 GHz
	Max. RF Power	8 dBm

[1] Vehicle height: From the ground to the top of the scooter.

[2] General range: Measured when there is no wind and at 77 ° F (25 ° C), the scooter is fully charged to ride at a constant speed of 9.3 mph (15 km/h) on a flat surface with a load of 165.3 lbs (75 kg).

[3] To recharge the battery, only use the battery charger provided in the package. Please see battery charger parameters in Specifications.