

TS-453BT3-8G

CPU	<p>Processor: Intel® Celeron® J3455 quad-core 1.5 GHz, burst up to 2.3 GHz</p> <p>Architecture: 64-bit</p> <p>Graphics: Intel® HD Graphics 500</p> <p>Encryption Engine: AES-NI</p>
System Memory	8 GB RAM (2 x 4 GB DDR3L)
Maximum Memory	8 GB (2 x 4 GB)
Memory Slot	2 x SODIMM DDR3L
Drive Bay	4 x SATA 6 Gbps
Drive Compatibility	<p>3.5-inch SATA hard disk drives</p> <p>2.5-inch SATA hard disk drives</p> <p>2.5-inch SATA solid state drives</p>
M.2 SSD Slot	2 x M.2 2280 SATA 6 Gbp/s SSD
SSD Cache Acceleration Support	<ul style="list-style-type: none"> • Drive bays 1 to 4 • M.2 slots 1 to 2 • Optional: SSD using PCIe expansion slot
Hot-swappable	<p>Yes</p> <p>The following are not hot-swappable: M.2 SSDs, SSD cache drives, SSDs using PCIe expansion slots.</p>
10 Gigabit Ethernet Port	1 x 10GBASE-T RJ-45
Gigabit Ethernet Port	2 x RJ45
PCIe Slot	<p>1 x PCIe 2.0 x2</p> <p>Note: Pre-installed with a QM2 expansion card that includes a 10GbE SFP+ port and two M.2 SSD slots).</p>
Thunderbolt Port	2 x Thunderbolt 3
USB Port	5 x USB 3.0 (Front: 1 x One Touch Copy; Back: 4)
HDMI Output	2 x HDMI 1.4b (up to 3840 x 2160 resolution at 30 Hz)
Audio	<ul style="list-style-type: none"> • 2 x 3.5 mm dynamic microphone jacks • 1 x 3.5 mm line-out jack • 1 x speaker <p>Note: You cannot use the speakers and the line-out jack simultaneously.</p>
Display Panel	Monochrome OLED display with capacitive sensing Enter and Select buttons
USB One Touch Copy	Front: USB 3.0 Type-A
IR sensor	QNAP RM-IR004 remote control (MCE compatible)
Form Factor	Tower

Dimensions (H x W x D)	168 x 170 x 226 mm 6.61 x 6.69 x 8.90 inch
Net Weight	2.51 kg (5.53 lbs)
Power Suply Unit	120W, 100-240V AC, 50/60Hz
Fan	System: 1 x 12 mm
Operating Temperature & Relative Humidity	0 to 40°C (32 to 104°F), 5 to 95% non-condensing, wet-bulb 27°C (80.6°F)
Security Slot	Kensington security slot

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.