Product data sheet Characteristics

PMH63VT-IT

APC Home/Office SurgeArrest 6 outlets with Phone and Coax Protection 230V Italy



Overview

Model Name	APC Home/Office SurgeArrest 6 outlets with Phone and Coax Protection 230V Italy
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Italy

Output

Number of Outlets	6
Receptacle Style	Italy

Input

Model Name	APC Home/Office SurgeArrest 6 outlets with Phone and Coax Protection 230V Italy
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Italy
Output	
Number of Outlets	6
Receptacle Style	Italy
Input	
Nominal Input Voltage	230V
Input Power	2300 W
Input Frequency	50 Hz
Input Connections	Italian CEI 23-16
Maximum Line Current per phase	0.0 A
Cord Length	3 meters
Maximum Input Current	10 A
Surge Protection and Filtering	
Surge energy rating	1836 joules
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40.0 dB
Peak Current Common Mode	48.0 kA
NM Surge Response Time (ns)	1.0 ns
Data Line Protection	Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector) , RJ-11 Modem/Fax protection
Physical	
Net Weight	0.81 kg
Maximum Height	62.0 mm
Maximum Width	272.0 mm

Surge Protection and Filtering

Surge energy rating	1836 joules	
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40.0 dB	_
Peak Current Common Mode	48.0 kA	- 7
NM Surge Response Time (ns)	1.0 ns	-7
Data Line Protection	Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector) . RJ-11 Modem/Fax protection	-

Physical

J		
Net Weight	0.81 kg	7
Maximum Height	62.0 mm	Ë
Maximum Width	272.0 mm	

Maximum Depth	110.0 mm
Shipping Weight	0.95 kg
Shipping Height	65.0 mm
Shipping Width	310.0 mm
Shipping Depth	165.0 mm
Master Carton Units	12.0
Master Carton Dimensions (Length x Width x Height)	14 x 13 x 16 inches
Master Carton Weight	5.47 kg
Color	White
Units per Pallet	96.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% non-condensing %
Operating Elevation	0-15000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters

Conformance

Approvals	CE
Standard warranty	Lifetime (European Union countries only)
Equipment protection policy	Lifetime: 75000 Euros

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs